

Seat Colors Black Vinyl

Body Color <sup>Red</sup>

COLDEN CITERICE CITERICE TOTC is easier than ever to transport! This new design creates a lightweight base that disassembles into two pieces with the heaviest piece weighing only 35 lbs! Model GP162 offers a compact turning radius with a robust 300 lb. weight capacity. For the consumer looking for high quality at a great value, nothing beats the all-new LiteRider PTC!



2

## LiteRider **ptc**

Model Number	GP162
Weight Capacity	300 lbs.
Drive Wheels	Rear
Maximum Speed	3.5 mph
Operating Range <sup>1</sup>	9.5 miles
Ground Clearance	2.5″
Turning Radius	26″
Type Batteries	2-18 AH
Colors	Red
Freewheel Mode	Yes
Electronic Speed Control	Yes
Electro-Mechanical Brakes	Yes
Charger	Off Board
Controller	PG VR-2 50 Amp Remote
Dimensions:	
Length	33″
Width	22.5″
Height (ground to top of back of seat)	33" - 34"
Height (ground to top of back of headrest)	N/A
Ground to Top of Seat	20.5" - 21.5"
Number of Seat Height Positions	2
Size of Increments	1.0″
Weight of Unit: (assembled)	116 lbs.
Front Half	34 lbs.
Rear Half	35 lbs.
Seat w/Arms	22 lbs.
Batteries	25 lbs/pack
Tires:	Flat Free
Drive Wheels	9″
Casters	6″
Anti-Tip Wheels	3″
Standard Seat:	Stadium Style
Slide Seat	N/A
Back Height - no headrest	16″
Back Height with headrest	N/A
Width x Depth	17″ x 16″
Color	Black Vinyl
Footrest:	Yes
Height adjustable	Yes
Height adjustable Angle adjustable	Yes Yes
Angle adjustable	
Angle adjustable Warranty:	Yes

<sup>1</sup> Battery range will vary due to rider weight, drive surface and terrain.

<sup>2.</sup> Electronics warranty excludes batteries.

## **Disassembles easily for transport!**



1. Remove seat



3. Grasp the frame and locking handle; lift the handle to unlock, and lift

the frame up and off the

drive train.



Perfect for transport!

## **Available Accessories:**

- Cane Holder Tube
- Oxygen Tank Holder
- Cup Holder
- Quad Cane Holder
- Walker Holder
- Crutch Holder
- Safety Flag
- Power Chair Cover
- Touch-up Paint
- Deluxe Pack N' Go
- Seat Belt (Optional)

Some accessories require a mounting bracket or mounting clips.

Literature is current at time of printing. Golden Technologies reserves the right to make changes to the product or literature at any time.



Golden Technologies • 401 Bridge Street, Old Forge PA 18518 • Tel: (800) 624-6374 • Fax: (800) 628-5165 • www.goldentech.com

SHT-GP162-090413